

NEW

Now available in the
KleenScreen™
 Range



COMPACT KLEENSCREENS

Where low intake velocities are not an environmental requirement

APPLICATIONS

- Ponds
- Galleries
- Irrigation Canals
- Anywhere where intake velocities are allowed to be up to 0.25 m/s

FEATURES

- SMALLER OVERALL SIZE FOR THE SAME FLOW**
- All the features and benefits of the standard Kleenscreen™ range
- Designed and manufactured in New Zealand
- Durable, lightweight, full stainless steel construction with thermoplastic bearings.
- Stainless Steel woven 10 mesh with 1.9mm holes, screen diameter 470mm
- The ultra-compact KSC20** can operate in water as shallow as 150mm deep!!



KSC95



KSC20

THE KSC RANGE

Model	Connection Size	Maximum Flow		Backwash flow		Backwash connection	Overall length
				Flow	Head		
KSC20	150NB Tab 'E'	20 L/s	72 m³/hr	0.9 L/s	25m	3/4" fem BSP	260mm
KSC40	150NB Tab 'E'	40 L/s	144 m³/hr	1.3 L/s	35m	3/4" fem BSP	435mm
KSC70	200NB Tab 'E'	70 L/s	252 m³/hr	1.8 L/s	40m	1" fem BSP	555mm
KSC95	250NB Tab 'E'	95 L/s	342 m³/hr	2.3 L/s	40m	1" fem BSP	680mm
KSC150	250NB Tab 'E'	150 L/s	540 m³/hr	3.3 L/s	40m	1" fem BSP	1045mm

Available from your local Kleenscreen supplier

Proudly brought to you by:

DAMA Manufacturing Ltd
 46A Weaver St
 WHANGAREI 0112
 NEW ZEALAND
 Ph: +64 27 493 3183, Fax: +64 9 926 1811
info@kleenscreen.com, www.kleenscreen.com